# **MODEL 2203 SERIES**

A flow controller is a differential pressure regulator designed to control minute gas flows with precision and keep a certain constant flow rate. Model 2203 Variable Secondary Pressure Flow Controller is a control valve that keeps mass flows at a constant rate under a given constant level of supply pressure even when the load pressure on the secondary side (outlet side) fluctuates, and its construction is designed so that the performance of its precision control over flows to the set flow rate is maintained by the incorporated precision needle valve without being affected by such fluctuations.

#### **Features**

- Stable flow control
- A non-rotary needle valve composed of high-precision components ensures smooth control of minute flows.
- Not subject to load pressure fluctuations
- The incorporated precision needle valve protects flows from being affected by secondary or outlet pressure fluctuations, so the product is a 'must-be' tool in the first stage of any flow control line.
- Cleanliness ensured
  - All the components are super-cleaned before assembly so that the product can be safely used even on instruments for analysis for which cleanliness is essential.

# **Applications**

- · Gas chromatographs
- Environmental instrumentation systems
- · Gas mixing systems in various fields

## **Standard Specifications**

Rated flow ranges	GAS: 10 ML/MIN-20 L/MIN
Control accuracy	Change in reading within 1.0% of change in load pressure (Inlet-outlet pressure difference must be at least 0.05 MPa.)
Number of turns of regulating screw	Approx. 12 turns
Maximum operating pressure	0.8 MPa
Maximum operating temperature	60°C
Materials of parts in contact with fluids	(A) Al, brass, POM, NBR (SS) SUS316, fluorocarbon resin, FKM
Connection end	Rc 1/8 (M8 + Rc 1/8)

#### **Optional Items**


- IN side filter joint Model 2300B
- Connection joint

#### Panel cut






#### **Dimensions**



### Notes:

- For information on available types of connection ends and filter joints other than those standard.
- You may specify the supply pressure, fluid and flow rate of your equipment for our selection of the type that most suits your requirements.
- Use the values on Table of Rated Flow Ranges for reference purposes only.

# **Ordering**



\* Refer to "Ordering" and "Illustrative example" when placing an order or requesting a quotation. Fill in the blanks in the "Order/Quotation Request Card" at the end of the catalog, and send the card by fax.